



Scheda di sicurezza
Spray lavaggio impianti
ELKE S.r.l.
VIA XXV APRILE 202 10042 NICHELINO (TO) ITALIA
REA di TO: 987683 P.Iva 08613670010
Tel. n.. +39 011 9622412

Safety Data Sheet dated 09/01/2017, version 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: SPRAY LAVAGGIO IMPIANTI
11.713

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

PRODUCT FOR AIR CONDITIONING.

PRODUCT FOR CLEANING AND WASHING.

Uses advised against:

do not use on humans and animals

1.3. Details of the supplier of the safety data sheet

Company:

ELKE S.r.l. Via XXV Aprile 202 10042 Nichelino (To) Italia.

Tel. n. +39 011 9622412

Competent person responsible for the safety data sheet:

Domenico Amosso info@elke-ac.com


1.4. Emergency telephone number


Centro Antiveleni Ospedale Niguarda Milano +39 02.66101029

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture


EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

 Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contents:

EPTANO PURO
propan-2-ol; isopropyl alcohol; isopropanol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

may form explosive vapor / air mixtures in places not well ventilated













SECTION 3: Composition/information on ingredients


3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
74.3 %	EPTANO PURO	Index 601-008-00-2 number: CAS: 142-82-5 EC: 205-563-8 REACH No.: 01- 2119666169- 27-XXXX	 2.6/2 Flam. Liq. 2 H225  3.2/2 Skin Irrit. 2 H315  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336  3.10/1 Asp. Tox. 1 H304  4.1/C2 Aquatic Chronic 2 H411 DECLP (CLP)*
16.1 %	propan-2-ol; isopropyl alcohol; isopropanol	Index 603-117-00-0 number: CAS: 67-63-0 EC: 200-661-7 REACH No.: 01- 2119457558- 25	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336
4.57 %	ANIDRIDE CARBONICA IN PACCHI	CAS: 124-38-9	 2.5/C Compr. Gas H280
2.69 %	GPL	CAS: 68476-40-4 EC: 270-681-9 REACH No.: 01-	 2.5/C Compr. Gas H280  2.2/1 Flam. Gas 1 H220

		2119486557-22-XXXX	DECLK (CLP)*
2.4 %	ethanol; ethyl alcohol	Index number: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6	 2.6/2 Flam. Liq. 2 H225

*DECLP (CLP): This substance is classified in accordance with Note P, Annex VI of EC Regulation 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Frostbite

CAP11

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

at work do not eat or drink.

do not smoke

avoid the accumulation of electrostatic charges

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)



Scheda di sicurezza
Spray lavaggio impianti
ELKE S.r.l.
VIA XXV APRILE 202 10042 NICHELINO (TO) ITALIA
REA di TO: 987683 P.Iva 08613670010
Tel. n.. +39 011 9622412

PRODUCT FOR AIR CONDITIONING.
PRODUCT FOR CLEANING AND WASHING.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

ACGIH - LTE(8h): 200 ppm - STE: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

ethanol; ethyl alcohol - CAS: 64-17-5

ACGIH - STE: 1000 ppm - Notes: A3 - URT irr

DNEL Exposure Limit Values

EPTANO PURO - CAS: 142-82-5

Worker Professional: 1100 mg/kg - Consumer: 640 mg/kg - Exposure: Human

Inhalation - Frequency: Short Term, local effects

Worker Professional: 1300 mg/kg - Consumer: 1200 mg/kg - Exposure: Human

Inhalation - Frequency: Short Term, systemic effects

Consumer: 180 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 840 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

emissions from production processes, including those from ventilation equipment should be inspected for the purposes of enforcement of environmental protection

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can	--	--
Odour:	of solvent	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	< 0 ° C	--	--

Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	> 2	--	--
Relative density:	0.75kg/l	--	--
Solubility in water:	undissolvable	--	--
Solubility in oil:	complete	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	(gas) > 400°C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	kv > 2,05 mm ² /s (a 40°C)	--	--
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

may form explosive vapor / air mixtures in places not well ventilated

10.4. Conditions to avoid

keep away from heat, sources of ignition
avoid the accumulation of electrostatic charges

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

by thermal decomposition can rid COx

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

EPTANO PURO - CAS: 142-82-5

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
c) serious eye damage/irritation:
Test: Eye Irritant - Route: Inhalation Mist - Species: Rabbit > 200 Ppm
h) STOT-single exposure:
Test: Inhalation Sensitization - Route: Inhalation Vapour Positive
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
GPL - CAS: 68476-40-4
a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat > 658 mg/l
ethanol; ethyl alcohol - CAS: 64-17-5
LD50 (RABBIT) ORAL: 6300 MG/KG
LD50 (RAT) ORAL SINGLE DOSE: 7060 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.
EPTANO PURO - CAS: 142-82-5

- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish 10 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia 4.5 mg/l - Duration h: 48
- b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia 2.6 mg/l - Notes: riproduzione
- c) Bacteria toxicity:
Endpoint: EC50 - Species: 1 15.41 mg/l - Duration h: 40 - Notes: inibizione della crescita
- e) Plant toxicity:
Endpoint: EC50 - Species: Algae 3.1 mg/l
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72
Endpoint: EC50 - Species: Fish > 100 mg/l - Duration h: 48
GPL - CAS: 68476-40-4
- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish Negative 19 mg/l - Duration h: 96
Endpoint: LC50 - Species: Daphnia Negative 14.2 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae Negative 7.7 mg/l - Duration h: 96



Scheda di sicurezza
Spray lavaggio impianti
ELKE S.r.l.
VIA XXV APRILE 202 10042 NICHELINO (TO) ITALIA
REA di TO: 987683 P.Iva 08613670010
Tel. n.. +39 011 9622412

- 12.2. Persistence and degradability
None
EPTANO PURO - CAS: 142-82-5
Biodegradability: N.A.Test: N.A.Duration: N.A.%: N.A.Notes: sostanza UVCB
- 12.3. Bioaccumulative potential
EPTANO PURO - CAS: 142-82-5
Bioaccumulation: N.A.Test: N.A.N.A.Duration: N.A.Notes: sostanza UVCB
- 12.4. Mobility in soil
EPTANO PURO - CAS: 142-82-5
Mobility in soil: N.A.Test: N.A.N.A.Duration: N.A.Notes: sostanza UVCB
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

- 14.1. UN number
ADR-UN number: 1950
IATA-Un number: 1950
IMDG-Un number: 1950
- 14.2. UN proper shipping name EPTANO PURO
- 14.3. Transport hazard class(es)
ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950
IATA-Class: 2.1
IMDG-Class: 2 Aerosols UN 1950
- 14.4. Packing group
ADR-Packing Group: III
- 14.5. Environmental hazards
Marine pollutant: Marine pollutant
- 14.6. Special precautions for user
IMDG-Page: 2102
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)



Scheda di sicurezza
Spray lavaggio impianti
ELKE S.r.l.
VIA XXV APRILE 202 10042 NICHELINO (TO) ITALIA
REA di TO: 987683 P.Iva 08613670010
Tel. n.. +39 011 9622412

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical
Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of
Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport
Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"
(ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.



Scheda di sicurezza
Spray lavaggio impianti
ELKE S.r.l.
VIA XXV APRILE 202 10042 NICHELINO (TO) ITALIA
REA di TO: 987683 P.Iva 08613670010
Tel. n.. +39 011 9622412

KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.